



PRW INDUSTRIES, INC.  
193 WEST ORANGETHORPE AVENUE  
PLACENTIA, CA 92870

TELE: (714) 792-1000  
TECH: (888) 377-9779

## SHAFT MOUNT ROCKER ARM SYSTEM INSTALLATION INSTRUCTIONS

FORD FE PRODUCTION/EDELBROCK PERFORMER CYLINDER HEADS

<b>PART #3339021/3339022 PARTS LIST</b>	
<b>ITEM</b>	<b>QUANTITY</b>
<i>Billet Aluminum Rocker Arms</i>	<i>16 each</i>
<i>Billet Aluminum Rocker Arm Stands/Numbered Pedestals</i>	<i>8 each</i>
<i>Billet Aluminum Rocker Arm Spacers</i>	<i>6 each</i>
<i>Hardened Steel Rocker Arm Shafts</i>	<i>2 each</i>
<i>Spring Steel Retainers – Rocker Shaft (3339021 only)</i>	<i>4 each</i>
<i>3/8”-16/24 x 3.50” Rocker Stand Studs – Full Shank</i>	<i>6 each</i>
<i>3/8”-16/24 x 3.50” Rocker Stand Studs – Undercut Shank</i>	<i>2 each</i>
<i>3/8”-16/24 x 3.75” Rocker Stand Studs – Undercut Shank</i>	<i>2 each</i>
<i>3/8” ID – Oil Stud Machined Washers – Black Oxide</i>	<i>2 each</i>
<i>3/8” - 24 – 12 Point Adjuster Flare Nuts</i>	<i>8 each</i>
<i>7/16”-20 – Valve Lash Adjusters – Ball-type</i>	<i>16 each</i>
<i>7/16”-20 – 12 Point Adjuster Flare Nuts</i>	<i>16 each</i>
<i>Stainless Steel Washers – Adjusters (16) &amp; Rocker Stands (6)</i>	<i>22 each</i>
<i>Push Rod Length Checker</i>	<i>2 each</i>

Thank you for purchasing a Performance Quotient® product. *PQ*<sup>2</sup>® Series Shaft Mount Rocker Arm Systems are engineered and manufactured by PRW Industries, Inc. to maximize valve train efficiency for many popular Chevrolet and other GM, Ford, and MOPAR performance aftermarket and racing cylinder heads. CNC machined billet steel or aluminum pedestals, centerless ground steel alloy rocker shafts, and PRW aviation quality fasteners comprise the foundation of *PQ*<sup>2</sup>® rocker arms and related systems. **PRW Ford FE Shaft Rocker Arm System** can be used with either hydraulic or mechanical camshaft or roller lifter combinations.

### ***PQ*<sup>2</sup>® Shaft Rocker Arm System Preparation:**

Please read these instructions *from start-to-finish* carefully before beginning your installation. Also, review the limited warranty information. If there are any questions or problems during the installation, please do not hesitate to call the PRW Customer Service Hotline at 1-888-377-9779, between the hours of 7 a.m. and 5 p.m. PST Monday through Friday.

- 1) Confirm that all parts are included by comparing to the parts list.
- 2) Make certain that you have all the tools necessary to complete the project.
- 3) Assembly lube and/or lubricating oil should be readily available for installation.

**SPECIAL NOTE:** PRW Ford FE Rocker Arm System is designed for high-performance and racing. As such, the installer must be prepared to deal with an increased volume of oil supplied to the valvetrain. Aftermarket and OEM heads alike may require the installation of oil restrictors in the oil passage ports numbers 3 and 6 near the base of the studs. As a general rule, cylinder head oil passage holes should be reduced (to .060”-.090” ID) by adding *restrictors\**; particularly when used in conjunction with a high pressure or high volume oil pump.

*\*The restrictor information should be used only as a guide. Actual restrictor diameters should be calculated and implemented (based upon other specifications/clearances deemed necessary) by the engine builder/installer.*

**PQ<sup>X</sup>® SHAFT MOUNT ROCKER ARM SYSTEM**  
**FORD FE PRODUCTION/EDELBROCK PERFORMER CYLINDER HEADS**

**PQ<sup>2</sup>® Ford FE Shaft Rocker Arm System Installation:**

**Step 1:** The rocker arm roller tips must be immersed in oil for at least 3 hours prior to installation. This will allow full lubricant penetration of the roller tip and axle. A disposable aluminum baking pan works well for this purpose.

**NOTE:** *It is critical to thoroughly pre-oil all shaft rocker components prior to use.*

**Step 2:** Thoroughly inspect both cylinder heads to ensure that there are no obstructions that may impair the rocker stands from bolting into place on an even plane.

**Step 3:** Utilize a thread chaser to assure the threads of the cylinder heads are clean and to insure the rocker stands will mount securely to the cylinder head.

**Step 4:** Verify that all rocker stand studs can be threaded to operational depths through the rocker shafts and stands and into the rocker arm stand stud holes, prior to applying torque to any of the rocker stand studs. Confirm adequate depth for rocker stand studs with calipers or depth gauge.

**Step 5:** The kit includes eight (8) numbered billet rocker stands. The billet stands are numbered to match with the corresponding cylinders 1, 2, 3 & 4 on the passenger side and 5, 6, 7, & 8 on the driver side. PN3339021 contains eight (8) single stands. PN3339022 contains four (4) single stands and four (4) double stands. The rocker arm system is pre-assembled with the aluminum spacers in their respective positions. Take some time to become familiar with the layout of the assembled parts and components before beginning the installation.

**Step 6:** When installing the rocker shafts, **be aware that the oil-feed holes must be facing down – towards the cylinder head.** This will ensure proper lubrication to the rocker arms. Otherwise, premature and excessive wear of the various components will undermine the integrity of the rocker arm system. Remove the socket head machine screws from the shafts, inspect for any debris, clean the central shaft and other oil passages, re-install and secure the socket head screws in the ends of each rocker arm shaft with thread locker.

**Step 7:** Start assembly from one end; working toward the opposite end of each cylinder head. Coat the inside bushing surface of each rocker arm with assembly lube (do not use Moly lube) before installing the rockers on the shaft, being careful not to mar the bushing surface in the process.

**Step 8:** Install the first rocker arm between the outer stand with the pedestal numbers facing towards the intake manifold. If using the double stands for cylinder numbers 1, 4, 5, and 8 the retaining clip is not included (*or required*) to secure the end rocker arms on the shaft. Only single stands require the retaining clip at each end. Continue the installation in cylinder order; working towards the opposite end of the head.

**NOTE:** *Both OE production and aftermarket heads require shims, using similar or different thicknesses between the pedestals or spacers on either side of the rocker arms to insure the roller tip of the rocker arm is properly aligned with the valve stem. Proper alignment may require a few trial installations, making certain that there is at least 0.005” clearance between each rocker arm and pedestal or spacer.*

**Step 9:** Install the studs finger-tight temporarily and check the rocker arm alignment on each cylinder head completing one head at a time. Each kit comes with 5 mounting studs per head with only 4 being necessary. There are six (6) full shank studs (for intake ports 1, 2, 4, 5, 7, and 8) and two (2) undercut shanks (oiling studs) that are tapered for oil flow (ports 3 and 6). OE production heads require a longer mounting stud for the oiling passage ports 3 and 6 (3.750” long). Edelbrock and other aftermarket heads require the same length studs at every location, with the oiling studs (3.50” long) used in the same location as the OE production heads.

**Step 10:** Once proper alignment has been confirmed, remove the rocker arm assembly keeping all shims intact. Remove the rocker stand studs.

**PQ<sup>X</sup>® SHAFT MOUNT ROCKER ARM SYSTEM**  
**FORD FE PRODUCTION/EDELBROCK PERFORMER CYLINDER HEADS**

**Step 11:** Apply removable strength thread locker (Loctite Blue 242 or similar) to the base of the rocker stand studs provided (course threaded end) and reinstall the studs hand tight. Heavy torque is not necessary when using thread locker. Assure that the studs are threaded completely into the mounting holes.

**NOTE:** *The mounting hole with the oiling passage requires the undercut stud. The OE Ford cast iron head requires the 3.750" undercut stud. Most aftermarket heads require the 3.500" undercut stud above intake ports 3 and 6 and the installation of oil restrictors.*

**Step 12:** Reconfirm rocker shaft oil holes are pointed down (towards the cylinder head). Double check the roller tip and valve stem alignment. Recheck to confirm at least .005" clearance between rocker bodies, rocker stands, and spacers. Install or remove shims as required. If installing PN3339021, affix the rocker shaft retainer clips to secure the end rocker arms, making certain that a shim (.015" or thicker thrust washer) is inserted between the end rocker arm and the retainer clip.

**Step 13:** Install the stud washers and nuts into place using PRW Moly lube (alternatively motor oil can be used if moly lube is unavailable). Tighten the nuts evenly across the assembly while applying pressure against the valve springs. Once the assembly is in place, torque the rocker stand nuts to 35 Lbs/Ft if using moly lube or 40-45 Lbs/Ft if using engine oil.

**Step 14:** If proper push rod length has already been determined install the pushrods into lifter bores, making certain that each pushrod is properly seated in the corresponding lifter body. Apply assembly lube sparingly on both the push rod seat and the ball adjuster. Now hand-turn the push rod adjuster insuring that the ball of the adjuster sits at the bottom of the pushrod cup.

If pushrod length has not been verified, please refer to the **Section: Pushrod Length; Checking to Determine Proper Length** to ascertain the appropriate pushrod lengths. Once completed, install the pushrods, and continue Step 15 as detailed below.

**Step 15:** Set valve lash per camshaft manufacturer's specification.

**SPECIAL NOTES:** Before running the engine, check for any interference between the rocker body and the pushrod. Check for interference and resolve any contact between the rocker body and the valve spring or retainer at any point during a cycle.

Prime the oil pump with an engine-priming tool and drill motor. Assure that oil is flowing through all valve train rocker arms, stands, spacers, and shims.

**Pushrod Length; Checking to Determine Proper Length**

1. With the number 1 cylinder at TDC (Top Dead Center) seat the provided pushrod length checkers in both exhaust and intake valve lifters.
  - a. *The base circle may be different between the intake and exhaust camshaft profiles.*
  - b. *It is necessary to check both for proper individual pushrod length.*
2. Begin with the valve lifter on camshaft base circle and valve lash adjuster rotated clockwise with 1 to 1 ½ threads exposed from the base of the rocker body over the number one cylinder and with the pushrod length checkers in place. *You may wish to mark the checkers "I" and "E" (for intake and exhaust) to easily identify after removal.*
3. Install Rocker Arm System on the cylinder head, securing with the washers and 12 point pedestal flare nuts. Tighten the stand until snug.
4. Adjust the pushrod length checkers to required fitment and proper length.
  - a. *Loosen the valve lash adjuster in the rocker body and then remove the pushrod length checkers.*
  - b. *Record the lengths required for reference and order the appropriate quality Intake and Exhaust pushrods from your Racing and Performance parts dealer.*

**PQ<sup>X</sup>® SHAFT MOUNT ROCKER ARM SYSTEM**  
**FORD FE PRODUCTION/EDELBROCK PERFORMER CYLINDER HEADS**

**NOTE:** Maximum recommended spring pressures for the PQ<sup>2</sup>® Shaft Mount Rocker Arm System is 275+ lbs for single stands and 375+ lbs for double-end stands. The rocker arms will clear up to 1.550" diameter valve spring. Pushrods selection is important; these are critical parts. High quality aftermarket 4130 chromoly steel pushrods are recommended. Custom length pushrods are readily available from PRW through your local dealer.

**Post Installation Maintenance:**

1. The synchronized oil system must be inspected periodically for obstructions that may prevent proper rocker arm oiling. After the valves have been adjusted to camshaft specifications, verify that each 12-pt adjuster nut has retained 25 Lbs/Ft torque.
2. After 500 miles of operation, recheck mounting stud nut torque and recheck the valve lash and lifter preload.

**NOTE:** Severe engine damage may occur if the adjuster nut should come loose while the engine is operating.

<b>TORQUE SPECIFICATIONS WITH OIL</b>	
<i>3/8" Rocker Stand Studs</i>	<i>20 Lbs/In (Hand Tighten)</i>
<i>3/8" Rocker Stand Flare Nuts</i>	<i>40-45 Lbs/Ft</i>
<i>7/16" 12 point Adjuster Flare Nuts</i>	<i>22-25 Lbs/Ft</i>

**WARNING:**

1. **Do not re-tap rocker body adjuster hole. Doing so will damage the rocker arm beyond repair!**
2. **Do not over-tighten adjuster nuts or modify adjuster counterbore!**
3. **Do not degrease rockers and/or run without proper lubrication.**
4. **Do not run valve lash adjusting screw out past two threads from seated position!**
5. **Do not allow pushrods to come in contact with cylinder head!**
6. **Do not run with rough or damaged pushrod tips!**
7. **Do not loosen shaft bolts under spring loads!**

**LIMITED WARRANTY**

Performance Quotient® and PRW Industries, Inc. ("PRW") warrants that all of its products are free from defects in material and workmanship, and against excessive wear for a period of (1) one year from the date of purchase. This **limited warranty** shall cover the original purchaser.

**PRW obligation under this warranty is limited to the repair or replacement of its product.** To make a warranty claim, the part must be returned within (1) one year of purchase to the address listed below, freight prepaid. Items covered under warranty will be returned to you freight collect.

It is the responsibility of the installer to ensure that all of the components are correct before installation. PRW assumes no liability for any errors relative to tolerances, component selection, or installation.

There is absolutely no warranty on the following:

- i. Any parts used in racing applications, or;
- ii. any product that has been physically altered, improperly installed or maintained, or;
- iii. any product used in improper applications, abused, or not used in conjunction with the proper parts.

**There are no implied warranties of merchantability or fitness for a particular purpose and no warranties which extend beyond the description of the face hereof.**

**PQ<sup>X</sup>® SHAFT MOUNT ROCKER ARM SYSTEM**  
**FORD FE PRODUCTION/EDELBROCK PERFORMER CYLINDER HEADS**

PRW shall not be responsible for incidental and consequential damages, property damage or personal injury damages to the extent permitted by law. Where required by law, implied warranties or merchantability and fitness are limited for a term of (1) one year from the date of original purchase. This warranty may give you specific legal rights. You may also have other legal rights, which vary from state to state.

**PRW INDUSTRIES, INC.**

193 WEST ORANGETHORPE AVENUE  
PLACENTIA, CA 92870

TELE: (714) 792-1000 FAX: (714) 792-1095  
TECH: (888) 377-9779

**WWW.PRW-USA.COM**

p:\product\installation guides\prw complete\pq2 ford fe shaft rocker arm system v1-5.doc