



"YOUR PARTNER IN PERFORMANCE"

For tech help, contact:

PRW

Toll Free (888) 377-9779

Installation Instructions

For

PRW Stud Mount Rockers Arms

Each Kit Contains:

- ◆ 16 *Rocker Arms*
- ◆ 16 *Rocker Arm Polylocks*

Installation

Step 1

After removing the rockers and other components from the package thoroughly wash each piece, and then blow dry.

Step 2

Prior to installation, submerge the rockers in engine oil for approximately 30 minutes to insure the roller tip and fulcrum are properly lubricated.

Step 3

Install the push rods. Make sure the pushrod is properly seated in the lifter. Fill each pushrod with engine oil, one at a time, as you install each rocker arm. This is to insure immediate lubrication when the engine is started and help prevent any galling. Also, apply a little molly lube to each push rod tip and all rocker arm push rod seats.

Step 4

Place rocker arms on the rocker arm studs, making sure the flat side of the fulcrum is facing up.

Step 5

Check for clearances. Make sure the rocker does not touch the lower portion of the rocker arm stud, guide plate, or the stud boss. Also, check the clearance between the spring and the body of the rocker. This should be a minimum of 0.040". Normally, the smallest amount of clearance occurs when the valve is closed and the lifter is at base circle. Always hand turn the crank to verify there is proper clearance of the rocker arm throughout the entire travel of the valve.

Step 6

Hand turn crankshaft in the running rotation until the exhaust pushrods begin to move upwards. This will bring the lifter to base circle and allow the intake valve for that cylinder to be adjusted.

Step 7

Intake Valves:

Hydraulic Lifter Cams: Hand tighten the adjusting nut until all slack between the rocker and pushrod is gone. Do this by turning the pushrod with your fingers as you tighten the polylock. Continue this until you feel a slight resistance in the spin of the pushrod. This process puts you at zero lash. At this point turn the polylock another ½ turn. Once adjusted hold the hex nut of the polylock and tighten the set-screw. Follow this procedure for all of the intake valves.

Solid Lifter Cams: Consult your cam spec sheet for proper lash specifications. With the proper feeler gauge between the roller tip and valve, tighten the polylock until you feel a slight drag on the feeler gauge.

Step 8

Exhaust Valves:

Hand turn the crankshaft until the intake pushrod has reached maximum lift and is between one half and two thirds of the way back down. The lifter is now at base circle enabling you to properly adjust the exhaust valve for that cylinder. Repeat step 7 for the remaining exhaust valves. When this is completed all the valves should be at proper pre-load position.

Step 9

Before installing the valve covers for the final time, check for proper clearance between rockers and valve covers. Then, pour a pint of engine oil over the rocker arms to insure proper lubrication. Finally, replace the valve covers on the heads.

If you need technical information, or additional information regarding the installation of this product,

call us toll-free at:

(888) 377-9779

Or

Email: tech@prwnetwork.com

Corporate Headquarters:

PRW Industries, Inc.

1081 North Batavia Street

Orange, CA 92867

Tele (714) 744-6200 · Fax (714) 744-9731

www.PerformanceRacingWarehouse.com